

Pultruded Moulded Grating Specifications.

Item	Height (mm)	Mesh (mm)	Open	Weight (kg/m ²)	Available size (mm)
1	13	38.1x38.1	72%	8	1220x3660
2	13	50.7x50.7	69%	7	1220x3660
3	22	19x19, 38x38	40%	15	1000x4038
4	25	40x40	67%	12.5	1007x3007, 1007x4047, 1247x4047
5	25	38.1x38.1	69%	12.5	1000x3000, 1000x4038, 1525x4007
6	25	38.1x38.1	54%	20	1000x3000, 1220x3660, 1000x4038
7	25	19x19, 38x38	40%	17.8	1220x3660
8	30	100x100	84%	8	1007x4007
9	30	40x40	67%	12.5	1007x3007, 1000x4033, 1247x4047
10	30	38.1x38.1	69%	15	1000x3000, 1000x4038, 1220x3660, 1525x4007
11	30	26x26, 52x52	52%	18	1000x4050, 1210x3670, 1500x2000, 1500x3000
12	30	20x20, 40x40	42%	19	1007x4047, 1247x4047, 1647x4047,
13	30	19x19, 38x38	40%	19	1000x3000, 1000x4038, 1220x3660
14	30	13x13, 40x40	32%	21.5	1007x3007, 1007x4047, 1247x4047
15	38	38.1x38.1	68%	19	1000x4038, 1220x3660, 1525x4046
16	38	25.4x152.4	56%	22.5	1226x3665 (bearing bars to run length direction)
17	38	26x26, 52x52	52%	21.8	1000x4050, 1210x3670, 1500x2000, 1500x3000
18	38	20x20, 40x40	42%	23	1007x4047, 1247x4047, 1527x4047
19	38	19x19, /38x38	40%	23.5	1000x3000, 1000x4038, 1220x3660
20	38	13x13, 40x40	32%	24.8	1007x3007, 1007x4047, 1247x4047
21	40	40x40	67%	21.5	1007x3007, 1007x4047, 1247x4047
22	50	50.7x50.7	69%	22	1225x3665,
23	50	50.7x50.7	69%	21.5	1530x4110
24	50	38.1x38.1	68%	32	1000x3000, 1000x4038, 1220x3660
25	52	26x26, 52x52	52%	29	1000x4060, 1210x3670
26	60	38.1x38.1	54%	50.5	1220x3660
27	70	38.1x38.1	54%	58	1230x3670
28	100	26x26, 52x52	52%	62	1010x3010